

# IMPORTANT - READ CAREFULLY

## HOW TO USE AND CARE FOR YOUR NEW MAGNETIC VEHICLE SIGNS

### Preparation For Installation

The vehicle surface and the brown, magnetic side of the sign should be cleaned and dried prior to applying.

### Installation

- Make contact on one edge of the sign to the vehicle surface in desired location. Then, let the adjacent part of the sign contact the vehicle surface until entire sign is held magnetically to the vehicle. If sign is not in desired position, remove and repeat process. (DO NOT try to straighten sign by pulling when it is held magnetically to the vehicle. This might scratch your vehicle. )
- Avoid placing your sign over chrome trim or surface protrusions of any kind.
- The temperature of the sign should be at least 60°F during installation. The temperature of the vehicle does not matter.

### Caution

Magnetic vehicle signs will not adhere to areas on your car where plastic body fillers have been used. In order to avoid losing your signs, use caution in applying vehicle signs to areas of your car that have been damaged.

### Maintenance

Your signs should be periodically removed - once a week minimum. Wipe dry both the vehicle and the back of the sign. Trapped moisture, dirt or chemicals may harm your vehicle finish. Clean your sign with plain water or warm water and a mild detergent.

### Storage

To avoid cracking or breaking, do not fold or crease. Store your magnetic sign flat.